

Yeast harvest in breweries with ITM-51

The Application

Yeast harvest automation in breweries using the ITM-51 turbidity sensor.

The Requirements

During fermentation, the yeast pitched into the wort multiplies two- to threefold through respiration of the oxygen dissolved in the wort. When the wort extract is fully fermented, the young beer is cooled down and the yeast settles in layers on the bottom or cone of the tank. The lowest, densest layer consists of dead yeast cells. The middle and still very dense layer consists of living yeast cells with a high fermenting power known as "white yeast". The upper layer, or light brown yeast, is mixed with beer and is less turbid (Fig. 1).

During the first yeast harvest, the bottom two layers are carefully extracted and separated because the white yeast is reused, or even marketed, as "pitching yeast".

During the storage and ageing period, the remaining yeast largely settles out as brown yeast.

When the tank is emptied, the brown yeast is carefully separated from the beer as this has a major impact on the beer quality.

Many breweries still monitor yeast harvesting manually. The process is controlled by checking the turbidity through a sight glass.

The Anderson-Negele Solution

Due to differences in the number of yeast cells and in the density of the yeast layers, turbidity measurement can be used to differentiate between the layers (Fig. 2). For this purpose, an ITM-51 turbidity sensor is installed at the fermentation tank outlet. It continuously measures the turbidity in % and outputs the measured value as a 4-20 mA analog signal to the process controller. By simply adjusting the setpoints, the yeast harvest can now be controlled precisely, reproducibly and automatically.

The Anderson-Negele Advantage

- Precise, reproducible measurements guarantee a consistent product quality.
- Time savings quickly amortize the cost of investment and make production more profitable on a lasting basis.
- Favorable price-performance ratio.

Fig. 2: Determination of Yeast Layers




Turbidity values in yeast layers
 Light brown 15 %
 Dark brown 20 %
 White 70 %
 Dead 80 %
 (approximate values)

ITM-51



Fig. 1: Fermentation tank with the measuring point



1. Fermentation tank
2. Young beer
3. Light brown yeast
4. White yeast
5. Dead yeast
6. ITM-51
7. Further processing

ITM-51_04014_2.1_en_na