

Product Information D3**FOOD**

D3 Differential Pressure & Level Transmitter


Range of applications

- Level in pressurized vessels with continuous process temperatures up to 110 °C (230°F)
- CIP/SIP at 135°C (275°F) for 1 hour when ambient is below 60 °C (140 °F)*
- Differential pressure measurement across filters

Application examples

- Level monitoring in yogurt culture vessels
- Level monitoring in fermentation vessels
- Grain bed monitoring in lauter tuns
- Level monitoring in brite tanks
- Pressure drop measurement across filters

Hygienic design/Process connection

- Front flush, 3-A installation for silos by Anderson flush fitting, E&H universal, or tank spud connections
- Conforming to 3-A Sanitary Standard 74-06 with Tri-Clamp® DIRECTadapt
- Product contacting materials compliant to FDA
- Sensor and product contact surfaces made of stainless steel
- Available with over 20 integral hygienic connections, more available through CLEANadapt adapters

Features

- Intuitive user interface makes set-up and configuration easy
- Electronic Differential provides 2 analog outputs (differential pressure and top or bottom pressure)
- State of the art temperature compensation minimizes error in dynamic temperature applications
- Fully electronic differential allows field replacement of components and repairability.
- Integrated tank tables allows volume and mass output when tank and product information are input
- Available in relative (vacuum and pressure)
- Dual o-ring seals provide IP69K ingress protection
- Dual loop output with graphical LCD display

Options/Accessories

- Optional digital remote kit making display easier to view
- Optional M12 molded cordset available
- Wide range of ranges and fittings available

Measuring principle of the pressure sensor

In the D3 system each sensor uses a piezoresistive transducer to measure the difference between the atmospheric and process pressures. Additionally, a temperature sensor measures the temperature of the transducer and fill fluid to provide an output compensation. The resistive temperature signal and the voltage signal from the transducer are inputs to a correction algorithm which provides a pressure output in digital form. The digital signal is transferred from each sensor to the head where the microprocessor determines the difference and converts the output to a 4-20mA signal for the difference and one for the head pressure or total system pressure depending on the user's selection.

* CIP/SIP temperature limit of 121°C (250 °F) for fitting options O88 and O89

Authorizations**Differential level sensor D3****Differential level sensor D3**

Specification		
Measuring range URL	Relative	-14.7...500 PSI, -1...35 BAR, -400...13850 inches of w.c.
Overpressure strength	Factor	1.5 x nominal pressure of measuring element
Measurement accuracy	Differential (PV) error	+/- 0.15% (DIFF _{URV} +TOP _{URV})
	Top/Bottom sensor (SV) error	+/-0.10% of calibrated range up to 5:1 turndown (+/-0.15% if over 5:1 turndown)
	Repeatability	0.05 %
	Long-term stability	0.2 % URL every 2 years
Temperature effect	Process	< 0.016 % of calibrated measuring range / 5.5 °C (10 °F)
	Ambient	< 0.016 % of calibrated measuring range / 5.5 °C (10 °F)
Temperature range	Process	-18...110 °C (0...230 °F), at ambient ≤ 71 °C (160 °F)
	Ambient	-18...71 °C (0...160 °F)
	CIP/SIP Cleaning	135 °C (275 °F) for 1 hour when ambient is below 60 °C (140 °F)*
Response time		< 0.2 seconds
Sample rate		< 0.05 seconds
Materials	Connection head	Stainless steel, AISI 304 (1.4301), R _a ≤ 0.8 μm (32 microinch)
	Metal cover	Stainless steel, AISI 304 (1.4301), R _a ≤ 0.8 μm (32 microinch)
	Plastic cover	Polycarbonate
	Threaded connector	Stainless steel, AISI 304 (1.4301), R _a ≤ 0.8 μm (32 microinch)
	Wetted parts	Stainless steel, AISI 316L, R _a ≤ 0.64 μm (25 microinch)
	Diaphragm	Stainless steel, AISI 316L, R _a ≤ 0.64 μm (25 microinch)
	Diaphragm seal/oil filling	Medical white oil / mineral oil / paraffin oil FDA approval number 21CFR172.878, 21CFR178.3620, 21CFR573.680 Neobee M20 (optional)
Process connection	3-A compliant	1.5", 2", 2.5", 3" Tri-Clamp® AIC CPM Flush Mount Anderson Flush Mount - Short and Long King Gage Flush Mount - Short, Medium and Long Rosemount/Foxboro Sanitary Spud - Short and Long Endress & Hauser Universal Adaptor - Short and Long
	not 3-A compliant	G1" CLEANadapt 1.5" NPT G1" Fixed Thread 38mm, 51mm SMS Liner (female) 40mm, 50mm DIN 11851 (Milk Coupling) M38x1.5 DRD
Electric connection	Cable gland	M16x1.5
	Plug-in connection	M12 plug, 5-pin, 1.4305
Approvals		3A CE Compliant CRN#OF19809.5 (consult factory for applicable regions and configurations) CAN/CSA-22.2 No. 61010-1 IP 69 K (with plug-in M12 connection) IP 67 (with cable gland) / NEMA 4X
Auxiliary Power Supply	Voltage	20...35 V DC
	Current Limit	4.2A
Output	Loop 1 (Differential)	analog 4...20 mA
	Loop 2 (Top or Bottom)	analog 4...20 mA
Tightening torque	For assembly all D3 components	27 Nm (20 ft-lbs)

* CIP/SIP temperature limit of 121°C (250 °F) for fitting options 088 and 089

Cleaning/Maintenance

- In case of using pressure washers, don't point nozzle directly to electrical connections!

Reshipment

- Sensors shall be clean and must not be contaminated with dangerous media! Note the advice for cleaning!
- Use suitable transport packaging only to avoid damage of the equipment!

Advice to conformity

- Applicable guidelines:
Electromagnetic compatibility 2004/108/EC
- The accordance with applicable EC-guidelines is confirmed with CE-labeling of the device.
- You have to guarantee the compliance of all guidelines applicable for the entire equipment.

Note on 3-A Sanitary Standard 74-

Information on installation according to 3-A standard is available on our website:
www.anderson-negele.com/3A74.pdf

Click on the PDF icon to download the document.

Transport/Storage

- No outdoor storage
- Dry and dust free
- Not exposed to corrosive media
- Protected against solar radiation
- Avoiding mechanical shock and vibration
- Storage temperature -55...+90 °C
- Relative humidity max. 95 %

Standards and guidelines

- You have to comply with applicable regulations and directives.

Disposal

- This instrument is not subject to the WEEE directive 2002/96/EC and the respective national laws.
- Pass the instrument directly on to a specialised recycling company and do not use the municipal collecting points.

Order code of fully assembled sensor

D3 Sensor assembled

Capillary fill

- 1 Mineral Oil (FDA approved)
- 5 Neobee M20

Top Sensor URL

- 5 0...6 PSI, 0...0.4 BAR, 0...166" w.c.
- 6 -14.7...30 PSI, -1...2 BAR, -400...830" w.c.
- 7 -14.7...100 PSI, -1...7 BAR, -400...2770" w.c.
- 8 -14.7...500 PSI, -1...35 BAR, -400...13850" w.c.

Top Sensor Fitting

XXX (See fittings table for 3 digit code)

Top Sensor Remote Cable

- 0 Integral (Compact version)
- A Remote with 1.5 m = 5' cable
- B Remote with 3.0 m = 10' cable
- C Remote with 4.5 m = 15' cable
- D Remote with 6.0 m = 20' cable
- E Remote with 7.5 m = 25' cable
- F Remote with 15 m = 50' cable

Bottom Sensor URL

- 5 0...6 PSI, 0...0.4 BAR, 0...166" w.c.
- 6 -14.7...30 PSI, -1...2 BAR, -400...830" w.c.
- 7 -14.7...100 PSI, -1...7 BAR, -400...2770" w.c.
- 8 -14.7...500 PSI, -1...35 BAR, -400...13850" w.c.

Bottom Sensor Fitting

XXX (See fittings table for 3 digit code)

Bottom Sensor Remote Cable

- 0 Integral (Compact version)
- A Remote with 1.5 m = 5' cable
- B Remote with 3.0 m = 10' cable
- C Remote with 4.5 m = 15' cable
- D Remote with 6.0 m = 20' cable
- E Remote with 7.5 m = 25' cable
- F Remote with 15 m = 50' cable

Enclosure cap

- 2 Clear cap
- 3 Stainless steel cap

Connector Locations

	Electric	Top Sensor	Bottom Sensor
1	A	B	C
2	A	C	B
3	B	A	C
4	B	C	A
5	C	A	B
6	C	B	A

Electrical connection

- A M12 QDR
- C Cable gland
- N 1/2" NPTF adaptor

Top Pressure Unit

- P PSI
- B BAR
- W inches of water
- L millibar

Top Pressure Range


- XXX See "Calibrated Range" table
- 999 Specify custom range
- 000 Full range of stem URL

Differential Output Unit

- P PSI
- B BAR
- W inches of water
- L millibar

Differential Output Range

- XXX See "Calibrated Range" table
- 999 Specify custom range
- 000 Full range of stem URL



D3 1 6 005 A 6 005 A 2 1 A P 060 W 294

Calibration range inches w.c.		
Code	Range	Stem URL
502	0...18	5
065	0...20	5
066	0...30	5
224	0...35	5
067	0...40	5
068	0...50	5
069	0...60	5
206	0...70	5
071	0...100	5, 6
294	0...140	5, 6
073	0...150	5, 6
074	0...160	5, 6
075	0...200	6
077	0...300	6, 7
078	0...350	6, 7
079	0...400	6, 7
503	0...415	6, 7
504	0...480	6, 7
081	0...500	6, 7
505	0...830	6, 7
084	0...1000	7
499	0...1200	7
506	0...1385	7, 8
507	0...1600	7, 8
086	0...2000	7, 8
508	0...3300	8
089	0...4000	8

Calibration range PSI		
Code	Range	Stem URL
025	-14.7...0	6
028	-14.7...15	6, 7
029	-14.7...30	6, 7
031	-14.7...60	7, 8
032	-14.7...100	7, 8
314	-14.7...200	8
501	0...1.2	5
428	0...1.5	5
057	0...2	5
235	0...3	5, 6
192	0...4	5, 6
060	0...6	5, 6
309	0...7	6
061	0...10	6, 7
502	0...18	6, 7
065	0...20	6, 7
066	0...30	6, 7
224	0...35	7
067	0...40	7
068	0...50	7, 8
069	0...60	7, 8
206	0...70	7, 8
071	0...100	7, 8
294	0...140	8
073	0...150	8
074	0...160	8
075	0...200	8
077	0...300	8
078	0...350	8
079	0...400	8
503	0...415	8
504	0...480	8
081	0...500	8

Calibration range BAR		
Code	Range	Stem URL
251	-1...1	6, 7
286	-1...2.5	7
217	-1...3	7
056	-1...4	7, 8
304	-1...7	7, 8
501	0...1.2	6, 7
428	0...1.5	6, 7
057	0...2	6, 7
235	0...3	7
192	0...4	7, 8
060	0...6	7, 8
309	0...7	7, 8
061	0...10	8
502	0...18	8
065	0...20	8
066	0...30	8
224	0...35	8

Calibration range mBAR		
Code	Range	Stem URL
224	0...35	5
067	0...40	5
068	0...50	5
069	0...60	5
206	0...70	5
071	0...100	5
294	0...140	5
073	0...150	5
074	0...160	5
075	0...200	5, 6
077	0...300	5, 6
078	0...350	5, 6
079	0...400	5, 6
503	0...415	5, 6
504	0...480	6
081	0...500	6
505	0...830	6, 7
084	0...1000	6, 7
499	0...1200	6, 7
506	0...1385	6, 7
507	0...1600	6, 7
086	0...2000	6, 7
508	0...3300	7
089	0...4000	7, 8

Note:

When multiple stem URLs are available (**Example 5,6**), lower stem URL is recommended (**Select 5**).

Order code of sensor stem

Stem version

- L3S Standard (HART)
- L3I Standard (IO-Link)
- L3P Pharmaceutical (HART)
- L3L Pharmaceutical (IO-Link)

Measurement range

- 5 0...6 psi, 0...0.4 bar, 0...166" w.c.
- 6 30 "Hg/0/30 psi, -1...2 bar, -400...830" w.c.
- 7 30 "Hg/0/100 psi, -1...7 bar, -400...2 770" w.c.
- 8 30 "Hg/0/500 psi, -1...35 bar, -400...13 850" w.c.

3-A compliant fittings

- 002 Tri-Clamp® 3/4"
- 004 Tri-Clamp® 1½"
- 005 Tri-Clamp® 2"
- 006 Tri-Clamp® 2½"
- 007 Tri-Clamp® 3"
- 123 AIC CPM Flush Mount*
- 088 Anderson Flush Mount Short (71060-A4, A6, A8)
- 089 Anderson Flush Mount Long (71060-A3, A5, A7, A9)
- 092 King Gage Flush Mount Long (1777-3)
- 093 King Gage Flush Mount Medium (1777-1, -6 Standard)
- 094 King Gage Flush Mount Short (1777-2 non-insulated)
- 141 Rosemount/Foxboro Sanitary Spud - Short
- 142 Rosemount/Foxboro Sanitary Spud - Long
- 154 Endress & Hauser Universal Adaptor - Short
- 155 Endress & Hauser Universal Adaptor - Long

Fittings not 3-A compliant

- 160 Flexibel thread G1", hygienic CLEANadapt
- 059 1½" NPT
- 182 G1" Fixed Thread
- 109 38 mm SMS Liner female
- 110 51 mm SMS Liner female
- 115 40 mm DIN 11851 (Milk Coupling)
- 124 50 mm DIN 11851 (Milk Coupling)
- 180 M38x1.5
- 181 DRD

*) Sensor is 3-A compliant when installed in a 3-A compliant instrument tee

Capillary fill

- 1 Mineral oil / FDA approved
- 5 Neobee / FDA approved

Sensor type

- 0 Integral (Compact version)
- A Remote with 1.5 m = 5' cable
- B Remote with 3.0 m = 10' cable
- C Remote with 4.5 m = 15' cable

- D Remote with 6.0 m = 20' cable
- E Remote with 7.5 m = 25' cable
- F Remote with 15 m = 50' cable

L3S 5 004 1 0

Order code of sensor head


D3E

Enclosure cap

- 2 Clear cap
- 3 Stainless steel cap

Connector Locations

	Electric	Top Sensor	Bottom Sensor
1	A	B	C
2	A	C	B
3	B	A	C
4	B	C	A
5	C	A	B
6	C	B	A



Electrical connection

- A M12 QDR
- C Cable gland
- N 1/2" NPT adaptor

Top Pressure Unit

- P PSI
- B BAR
- W inches of water
- L millibar

Top Pressure Range

- XXX See "Calibrated Range" table
- 999 Specify custom range

Differential Output Unit

- P PSI
- B BAR
- W inches of water
- L millibar

Differential Output Range

- XXX See "Calibrated Range" table
- 999 Specify custom range
- 000 Full range of stem URL

D3E 2 1 A P 060 W 294

Cord Sets

Shielded Molded w/10' cable	42117H0010
Shielded Molded w/25' cable	42117H0025
Shielded Molded w/50' cable	42117H0050
Shielded Molded w/100' cable	42117H0100

Weld-In Shells for Anderson Flush Mount (316L)

Anderson Long - Insulated Standard Vessel	71060A0003
Anderson Short - Uninsulated Standar Vessel	71060A0004
Anderson Long - Insulated Pressure Vessel	71060A0005
Anderson Short - Uninsulated Pressure Vessel	71060A0006
Anderson Long - Insulated H/D Pressure Vessel	71060A0009

Tank Shell Plugs (Supplied with nut and gasket)

Anderson Long	56511B0001
Anderson Short	56511B0002
Cherry Burrell Long	56511A0001
Cherry Burrell Short	56511A0002
King Long	56511C0001
King Medium	56511C0002
King Short	56511C0003

Flush Mount Calibration Adapters

Anderson Fitting	73198A0001
Cherry Burrell Fitting	73198A0002
King Gage Fitting	73198A0003

Gaskets for Flush Mount Fittings

Anderson - Silicone (3A, USP Class VI)	44348A0002
Cherry Burrell - Silicone	44292B0001
Endress & Hauser	45352B0001
King Gage - Silicone O-Ring	36240S3212
Rosemount - Silicone O-Ring	36240S3341

Other Accessories

Clear Cap w/gaskets	5632800001
Stainless Steel Cap w/gaskets	5632900001
M12 Quick Disconnect Receptacle	SP56726A0004
Cord Grip	SP5633100000
1/2" NPTF adaptor	SP5633200000
Seal Kit (6) gaskets	5633000001
Field Wireable Connector-Straight	42119B0000
Field Wireable Connector-90°	42119A0000
5' Remote Kit	73228A0005
10' Remote Kit	73228A0010
15' Remote Kit	73228A0015
20' Remote Kit	73228A0020
25' Remote Kit	73228A0025
50' Remote Kit	73228A0050
Rosemount/Foxboro Clamp Connection	46600A0001

