

Precise level measurement even with difficult media and operating conditions

Continuous Level Sensor NSL-F

Benefits in production processes

For efficient production processes, continuous, precise monitoring of the filling level of feed tanks, storage tanks or fillers is essential. The flexible, modular level sensor NSL-F with its potentiometric measuring principle offers a reliable and precise application even with difficult to measure media and with demanding applications such as:

- strongly or differently foaming media
- pasty media or media adhering to the measuring rod
- pressurized tanks
- fast level changes, e.g. during filling processes
- non-metallic tanks
- different media in one tank
- tank shapes with restricted installation access
- production environments with high mechanical or chemical stress (e.g. cleaning agents)

Advantages of the NSL-F sensor

- **Maximum resource efficiency due to precise measurement even with demanding media:** Even with foam or with the measuring rod coated by pasty or strongly adhesive media, the **measuring accuracy is < 1%** of the rod length.
- Ready for industry 4.0: **digital IO-Link interface and analog 4...20 mA** data transmission in parallel
- **Ideal for metallic, non-metallic and pressurized tanks** due to rod length from 50 mm to 3 m, installation from below, above or from the side and optional versions
- **Extremely fast response time < 100 ms** for precise dosing monitoring, e.g. for filling systems
- **Automatic adjustment to media**, no adaptation required with alternating media in one tank
- **Hygienic alternative to float sensors** due to easily sterilizable installation solution
- **Robust construction** made entirely of stainless steel

Typical customer applications

- Dairies / milk production: milk heaters, separators, fillers, ice cream production plants, tanks for yoghurt and pasty milk products
- Breweries: Brewing, lautering and storage tanks, filters, bottling plants
- Beverage and food industry: Filling systems for alternating beverages and juices, storage and production tanks



Optional versions



Technical specification at a glance

- **Extremely precise, fast & flexible** level sensor
- **Flex Hybrid Technology** with **digital + analog** interface (IO-Link + 4...20 mA)
- Modular design: configurable from the **low-priced to the fully equipped high-end model**
- For vessels from **50 mm to 3 m** height
- CIP / SIP cleaning up to **143 °C / 120 min.**
- **Response time < 100 ms** for constantly precise values even with rapid level changes in high-speed fillers
- **Protection class IP 69K** for safe application
- **Smart Replace Design:** Easy replacement of all components by plug & play

Modular Sensor platform with IO-Link and 4...20 mA

The **Flex-Hybrid Technology with IO-Link and 4...20 mA** combines the best of both worlds: Data from the sensor can be transmitted digitally, analogously or in parallel. The bidirectional communication enables status control and preventive maintenance at any time to avoid production downtimes. Installation and commissioning are time- and cost-saving thanks to plug-and-play technology, and sensor replacement is easier than ever before thanks to "Smart Replace Design" with automatic detection, configuration and parameterization.

Order code	
NSL-F-00	Potentiometric level sensor, straight version
Rod length EL	
0050...3000	In steps of 10 mm, intermediate sizes at extra charge
Process connection (Ⓐ: 3-A compliant)	
S00	CLEANadapt G1/2" hygienic Ⓐ
S01	CLEANadapt G1" hygienic Ⓐ
TC1	Tri-Clamp 1½" Ⓐ
TC2	Tri-Clamp 2" Ⓐ
T25	Tri-Clamp 2½" Ⓐ
TC3	Tri-Clamp 3" Ⓐ
V10	Varivent type B, DN 10/15
V25	Varivent type F, DN 25 Ⓐ
V40	Varivent type N, DN 40/50 Ⓐ
Material certificate	
O	No certificate
Z	With 3.1 material certificate
Mounting position	
1	Installation from top, head orientation horizontal
2	Installation from top, head orientation vertical
3	Installation from bottom, head orientation horizontal
4	Installation from bottom, head orientation vertical
5	Installation from top, head orientation horizontal, 40 mm insulation, only for EL ≥ 200 mm
6	Installation from top, head orientation vertical, 40 mm insulation, only for EL ≥ 200 mm
Signal module	
A42	1x 4...20 mA level
I42	IO-Link and 1x 4...20 mA level
Electrical connection	
P	Cable gland M16x1.5
M	1x M12 plug, 4 pin output/power supply
L	1x M12 plug, 5 pin, wiring according to LN sensor
C	1x M12 plug, 5 pin analog output and IO-Link
Display	
X	Without display
S	Simple User Interface with small display
L	Large User Interface with display
Cap	
X	Opaque plastic
P	Clear plastic
M	Stainless steel without control window
W	Stainless steel with control window
Insulation at rod end	
XX	Without insulation
PK	With PEEK insulation >> EL + 30 mm
Configuration	
X	Factory setting
S	Special customer setting
Note:	
Order code for optional versions see product information:	
Remote:	NSL-FR
Curved:	NSL-F-01
Double rod:	NSL-F-02
NSL-F-00 / 1500 / S00 / O / 1 / A42 / P / X / X / XX / X	

60013 / 1.1 / 2021-06-28 / MH

NEGELE MESSTECHNIK GMBH
 Raiffeisenweg 7
 87743 Egg an der Guenz

Phone +49 (0) 83 33 . 9204 - 0
 Fax +49 (0) 83 33 . 9204 - 49
 sales@anderson-negele.com

Tech. Support
 support@anderson-negele.com
 Phone +49 (0) 83 33 . 9204 - 720